



REITECH CORPORATION

3146 Marion Avenue, Reading, Pa. 19605
Phone: 610-929-9451 E-mail: info@reitechcorporation.com

R3R1021 TOLUIDINE RED YS - (PR-3) DISPERSION

R3N566 Toluidine Red YS is a highly pigmented, finely ground resinated dispersion. It is a popular low cost pigment with good tinting strength and full-tone light fastness. It is not recommended for exterior paints, especially in tint form.

Its major uses are for interior emulsion, masonry, trim, bill board, and machinery paints, poster printing inks, wallpaper, paper, artist's colors and other applications requiring high pigmentation levels.

Generic Name:	CI Pigment Red 3
Constitution Number:	CI 12120
Common Name:	Toluidine Red
CAS#:	2425-85-6
Pigment Type:	Organic
Resin Type:	Acrylic
Dispersing Agent:	Anionic / Nonionic
Percent Pigment:	48.00%
pH:	8.5 – 9.5
Total Solids:	56.08% ± 2%
VOC:	1.08% typical
Specific Gravity:	1.19 +/-5%
Weight per gallon:	9.88#/Gallon +/- 5%

DISCLAIMER: SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE, except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States patent. Buyer must assume responsibility for the determination of the suitability of the product for uses and applications contemplated by the Buyer or any applications or use of the buyer's customer. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether based on contract, breach of warranty, negligence or otherwise, shall be greater in amount than the purchase price of the quantity of the product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.

5/21/2013